

411.2 Professional Shredder

Large volumes of data media are shredded without problems on all office floors. This professional series workhorse is suitable for a 20–25 person office.



Crosscut (cc)
Strip cut (sc)
Green info=can shred.
Red info=cannot shred.



except
HS Level 6



sc cuts:
1/4" • 1/8"
cc cuts:
1/8" x 2" • 1/16 x 5/8"



sc cuts:
1/4" • 1/8"
cc cuts:
1/8" x 2"



sc cuts:
1/4" • 1/8"
cc cuts:
1/8" x 2"

- Keypad for constant operation and reverse.
- Hardened steel cutters can handle occasional standard paper clips or staples.
- Crosscut models can cut up to approximately 40 sheets per run; Strip cut: up to 67 sheets per run (see specifications).
- Practical storage space with optional paper trays for paper stacks. (Paper trays available for purchase).
- Auto stop when container is full or door is open. Convenient pull-out system for removing the integrated, sturdy, reusable shred-bin bag.
- Powerful, specially adjusted motor for longer periods of use — with thermal protection for high performance.
- The tried-and-tested closed-tooth wheel drive prevents penetration of dirt and slows wear, increasing the service life.
- Enclosed housing protects against the spread of paper dust and provides for "whisper quiet" shredding.
- Heavy-duty castors for effortless mobility.
- Crosscut shredders should be oiled to maintain top working condition.

Specifications	Strip Cut	Cross Cut
Cutting size	1/4" • 1/8"	1/8" x 1 1/2" • 1/16" x 5/8" • 1/32" x 7/16" • 1mm x 5mm
Security level	2 • 2	3 • 4 • 5 • HS Level 6
Cutting capacity per run in sheets, 70 g/m ² 80 g/m ²	65–67 • 48–50 51–53 • 38–40	38–40 • 26–28 • 17–19 • 9–10 33–35 • 20–22 • 12–14 • 7–8
Cutting speed	24 ft./min.	24 ft./min.
Throat opening	16"	16"
Motor at max. no. of sheets	2100W	2100W
Voltage	115 V/60 Hz	115 V/60 Hz
Dimensions (W x D x H)	23.4" x 18.5" x 37.8"	23.4" x 18.5" x 37.8"
Weight	163 lbs	181 lbs.
Shred-bin volume	38.5 gallons	38.5 gallons

All technical specifications are approximate values.
Technical and design modifications reserved.

Copyright © 2006 by HSM® of America

For Customer Service call: 800-613-2110
www.hsmofamerica.com

HSM®